## IN THE SPECIFICATION

Please replace the paragraph at page 10, lines 7-21, with the following rewritten paragraph:

FIG. 2 shows the image forming units 21M through 21BK in detail. Because the image forming units 21M through 21BK are identical in configuration except for the dolor color of toner to use, let the following description concentrate on the image forming unit 21M by way of example. As shown, the image forming unit 21M includes a photoconductive drum of image carrier 25M. Sequentially arranged around the drum 25M, as named in the direction of rotation of the drum 25M (clockwise), are a charger 27M, a developing device 26M, and a cleaning device 28M. A light beam 29M, issuing from a writing unit 29, scans the surface of the drum 25M imagewise at a position between the charger 27M and the developing device 26M. The drum 25M may be replaced with any other suitable image carrier, e.g., a photoconductive belt.

Please replace the paragraph at page 12, lines 15-21, with the following rewritten paragraph:

The sheet, carrying the full-color toner image thereon, is then separated from a drive roller, labeled 22A1 in FIG. 2, included in the image transferring unit 22 on the basis of curvature. Subsequently, the full-color toner image is fixed on the sheet by the fixing unit 1, FIG. 1. The sheet is then conveyed to either one of print trays 32 and a tray such as print tray 33 in a simplex print mode.